

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
11 March 2004 (11.03.2004)

PCT

(10) International Publication Number
WO 2004/021530 A1

(51) International Patent Classification: H01S 3/10

(21) International Application Number:
PCT/EP2002/009675

(22) International Filing Date: 30 August 2002 (30.08.2002)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): AGILENT TECHNOLOGIES, INC. [US/US]; 395 Page Mill Road, Palo Alto, CA 94306 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): SCHWARZ, Jochen [DE/DE]; Pilsener Strasse 10, 70567 Stuttgart (DE).

(74) Agent: BARTH, Daniel; c/o Agilent Technologies Deutschland GmbH, Patentabteilung, Herrenbergerstrasse 130, 71034 Böblingen (DE).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: WAVELENGTH TUNABLE RESONATOR WITH A PRISM



(57) Abstract: A wavelength tunable resonator comprises a first reflector (10) for reflecting an incident beam (5) of electromagnetic radiation towards a second reflector, said second reflector (50), said second reflector (50) for reflecting said beam (5) back towards said first reflector (10), said first and second reflector defining a resonator having an optical path with a length, a gain medium (20) for generating and emitting said beam (5) towards said first and second reflector (10 50), said laser source being arranged within said resonator, a prism (40), which is arranged within said optical path, serving to filter a wavelength of said beam (5) of electromagnetic radiation and being designed to redirect a portion of said incident beam comprising said filtered wavelength towards said second reflector (50), wherein said second reflector is arranged to be movable with respect to other optical elements within said resonator for increasing or decreasing said length of said optical path of said resonator, and wherein said prism (40) is arranged to be rotatable about an axis (110) with respect to said other optical elements within said resonator for adapting said filtered wavelength to said increase or decrease of said optical path length.

WO 2004/021530 A1

BEST AVAILABLE COPY